

Technical data sheet

General data	
Frame size	90
Housing material	Aluminum with iron shields
Install model	According to the standard
Type of feet	Removable feet
Net weight	13.5 kg
Insulation class	F
Protection degree	IP 55
Thermal protection	Bimetallic sensor
Rotation direction	Clockwise
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M20 × 1.5
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	0.75	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
Rotation speed	890	RPM @ 50Hz
Rated current	4.93	A (In) @ Δ 50Hz
Starting current	2.4	×In
Rated torque	8.05	Nm (Mn)
Starting torque	0.65	×Mn
Breakdown torque	1.5	×Mn
Efficiency	67.5	@ 100% load @ 75% load @ 50% load
Power factor cosφ	0.98	@ 100% load

Mechanical data		
Bearings brand	C&U	
Bearings type	6205 2RZ C3 6205 2RZ C3	(DE) (NDE)
Lifetime of bearings		20000 hours
Allowed radial load		926 N
Allowed axial load		802 N
Run capacitor	40 μF / 450 V	
Moment of inertia	0.003523	Kg*m ²
Noise level	70	dB(A)