

Technical data sheet

General data	
Frame size	100
Housing material	Aluminum with iron shields
Install model	According to the standard
Type of feet	Removable feet
Net weight	17.2 kg
Insulation class	F
Protection degree	IP 55
Thermal protection	Bimetallic sensor
Rotation direction	Clockwise
Service duty	S4-80% 30c/h
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M20× 1.5
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitute	1000 m above sea level

Electrical data		
Output	0.75	kW
Frequency	50	Hz
Voltage (±5%)	230	V Δ @ 50Hz
	400	V Y @ 50Hz
	276	V Δ @ 60Hz
	480	V Y @ 60Hz
Rotation speed	700	RPM @ 50Hz
	840	RPM @ 60Hz
Rated current	3.71	A (In) @ Δ 50Hz
	2.13	A (In) @ Y 50Hz
Starting current	4.4	×In
Rated torque	10.23	Nm (Mn)
Starting torque	2.1	×Mn
Breakdown torque	2.55	×Mn
Efficiency	75.2	@ 100% load
	74.8	@ 75% load
	70.8	@ 50% load
Power factor cosφ	0.68	@ 100% load

Mechanical data		
Bearings brand	C&U	
Bearings type	6206 2RZ C3	(DE)
	6206 2RZ C3	(NDE)
Allowed radial load		1437 N
Allowed axial load		1247 N
Moment of inertia	0.00604	Kg*m ²
Noise level	59	dB(A)