

Technical data sheet

General data	
Frame size	160
Housing material	Casting iron
Install model	According to the standard
Type of feet	Fixed feet
Net weight	115 kg
Insulation class	F
Protection degree	IP 55
Thermal protection	3x PTC 150°C
Rotation direction	Clockwise
Service duty	S4-80% 30c/h
Vibration level	A
Balance	Half-key balanced
Cable glands	2x M36
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	11	kW
Frequency	50	Hz
Voltage (±5%)	400 690 480 828	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	1460 1752	RPM @ 50Hz RPM @ 60Hz
Rated current	20.5 11.9	A (In) @ Δ 50Hz A (In) @ Y 50Hz
Starting current	7.5	×In
Rated torque	72.00	Nm (Mn)
Starting torque	2.3	×Mn
Breakdown torque	2.6	×Mn
Efficiency	91.0 90.5 90.2	IE2 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.85	@ 100% load

Mechanical data		
Bearings brand	SKF Explorer	
Bearings type	6309 C3 6309 C3	(DE) (NDE)
Allowed radial load	1769 N	
Allowed axial load	21200 N	
Lubrication interval of NDE bearing	21500 h	
Lubrication interval of DE bearing	21500 h	
Moment of inertia	0.103000	Kg*m ²
Noise level	73	dB(A)