

Technical data sheet

General data	
Frame size	112
Housing material	Aluminum with iron shields
Install model	According to the standard
Type of feet	Removable feet
Net weight	35.7 kg
Insulation class	F
Protection degree	IP 55
Thermal protection	Bimetallic sensor
Rotation direction	Clockwise
Service duty	S4-80% 30c/h
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M25× 1.5
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	5.5	kW
Frequency	50	Hz
Voltage (±5%)	400	V Δ @ 50Hz
	690	V Y @ 50Hz
	480	V Δ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	1435	RPM @ 50Hz
	1722	RPM @ 60Hz
Rated current	11.23	A (In) @ Δ 50Hz
	6.51	A (In) @ Y 50Hz
Starting current	7.2	×In
Rated torque	36.6	Nm (Mn)
Starting torque	2.5	×Mn
Breakdown torque	2.95	×Mn
Efficiency	85.9	@ 100% load
	87.1	@ 75% load
	86.6	@ 50% load
Power factor cosφ	0.82	@ 100% load

Mechanical data		
Bearings brand	C&U	
Bearings type	6306 2RZ C3	(DE)
	6206 2RZ C3	(NDE)
Allowed radial load		1579 N
Allowed axial load		1285 N
Grease type	1285	
Moment of inertia	0.01423	Kg*m ²
Noise level	68	dB(A)