

Technical data sheet

General data	
Frame size	112
Housing material	Aluminum with iron shields
Install model	According to the standard
Type of feet	Removable feet
Net weight	42.2kg
Insulation class	F
Protection degree	IP 55
Thermal protection	Bimetallic sensor
Rotation direction	Clockwise
Service duty	S4-80% 30c/h
Vibration level	A
Balance	Half-key balanced
Cable glands	2 - M25× 1.5
Cooling	IC 411
Painting color	RAL 5010
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	7.5	kW
Frequency	50	Hz
Voltage (±5%)	400	V Δ @ 50Hz
	690	V Y @ 50Hz
	480	V Δ @ 60Hz
	828	V Y @ 60Hz
Rotation speed	2920	RPM @ 50Hz
	3504	RPM @ 60Hz
Rated current	14.3	A (In) @ Δ 50Hz
	8.29	A (In) @ Y 50Hz
Starting current	7.5	×In
Rated torque	24.53	Nm (Mn)
Starting torque	2.0	×Mn
Breakdown torque	2.2	×Mn
Efficiency	86.0	@ 100% load
	87.1	@ 75% load
	84.7	@ 50% load
Power factor cosφ	0.88	@ 100% load

Mechanical data		
Bearings brand	C&U	
Bearings type	6306 2RZ C3	(DE)
	6206 2RZ C3	(NDE)
Allowed radial load		1252 N
Allowed axial load		950 N
Moment of inertia	0.00743	Kg*m ²
Noise level	78	dB(A)