

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4520SB
	Description	Polymer concrete channel MOD. BASE 200, c/w S235JR steel inlay pressure-locked grating, 40x2-10x2, 33x33 mesh, installed and locked, hot-dip galvanised. Channel average runoff section sqcm. 315. Load class B125 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	Intended use or uses of the product	-
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	-
6	Standard	-
	First year of marking	-
	Notified Body	-
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	B125 - EN 1433:2008
	Permanent set	-
	Durability	-
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, - DOP N. 4520SB Rev.-		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator 