

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4F00SB
	Description	Vibro-compressed concrete channel MOD. VIBRO-BASE 100 (H1), H140 mm,c/w S235JR steel inlay pressure-locked grating, 30x2-10x2, 33x22 mesh, installed and locked, hot-dip galvanised. Channel average runoff section sqcm. 99. Load class B125 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	System 3
6a	Standard	EN 1433:2008
	Notified Body	IGQ - Milano (MI)
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	B125 - EN 1433:2008
	Permanent set	<CO/50 - Cap. 7.16 Norm 1433:2008
	Durability	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, 01/08/2016		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
Rev.1		