

**DECLARATION OF PERFORMANCE - CPR 305/2011**

<b>1</b>	<b>Unique code of the product</b>	4F10SA
	<b>Description</b>	Vibro-compressed concrete channel MOD. VIBRO-BASE 150 (H1), H200 mm, c/w S235JR steel inlay pressure-locked grating, 20x2-10x2, 33x33 mesh, installed and locked, hot-dip galvanised. Channel average runoff section sqcm. 223. Load class A15 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
<b>2</b>	<b>Intended use or uses of the product</b>	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
<b>3</b>	<b>Manufacturer</b>	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
<b>4</b>	<b>Agent</b>	ND
<b>5</b>	<b>System of AVCP</b>	System 3
<b>6</b>	<b>Standard</b>	EN 1433:2008
	<b>First year of marking</b>	2016
	<b>Notified Body</b>	Istituto Giordano 00019 - Bellaria (RN)
<b>Declared performance</b>		
<b>7</b>	<b>Essential characteristics</b>	<b>Performance</b>
	<b>Watertight</b>	No loss
	<b>Loading capacity:</b>	
	<b>Maximum load</b>	A15 - EN 1433:2008
	<b>Permanent set</b>	<CO/50 - Cap. 7.16 Norm 1433:2008
	<b>Durability</b>	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
<b>8</b>	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, -		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4F10SA Rev.-		