

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4F10T3
	Description	Galvanized steel brickslot cover mod. THIN H120, th. 20/10, with 15 mm central slot, height 120+20 mm, for channels MOD. VIBRO-BASE 150.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	System 3
6a	Standard	EN 1433:2008
	Notified Body	Ecam Ricert srl- Monte di Malo (VI)
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	D400 - EN 1433:2008
	Permanent set	<CO/300 - Cap. 7.16 Norma 1433:2008
	Durability	Galvanized surface as per standard EN ISO 1461. Galvanizing durability according to EN ISO 14713.
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, 01/09/2018		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4F10T3 Rev.1		