

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4G33SX4
	Description	Polymer concrete channel MOD. POLY FLY 300 HIGH, H345 mm, with AISI 304 stainless steel protective edge rails, c/w AISI 304 stainless steel pressure-locked grating, 50x3-10x2 33x33 mesh, pickled, installed and locked. Channel runoff section sqcm. 855. Load class D400 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	System 3
6	Standard	EN 1433:2008
	First year of marking	2016
	Notified Body	Istituto Giordano 00019 - Bellaria (RN)
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	D400 - EN 1433:2008
	Permanent set	<CO/300 - Cap. 7.16 Norm 1433:2008
	Durability	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, 09/04/2021		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4G33SX4 Rev.1		