

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4R00S
	Description	Vibro-compressed concrete channel MOD. R122, with galvanized steel protective edge rails, suitable for grating dim. 122x1000 H20 mm. Channel runoff section sqcm. 45. Load class C250 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	System 3
6	Standard	EN 1433:2008
	First year of marking	2016
	Notified Body	Istituto Giordano 00019 - Bellaria (RN)
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	C250 - EN 1433:2008
	Permanent set	<CO/50 - Cap. 7.16 Norm 1433:2008
	Durability	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, 01/08/2016		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4R00S Rev.1		