

DECLARATION OF PERFORMANCE - CPR 305/2011

16

1	Unique code of the product	4R02MGP	
	Description	Press-locked grating panel, in S235JR UNI EN 10025-2:2019 steel, bearing bar 25x2, transverse bar 10x2, mesh 33x33, with C shaped edge, hot-dip galvanized, for locking at R210 drain channel. Loading class C250 UNI EN 1433:2008.	
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.	
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it	
4	Agent	ND	
5	System of AVCP	Sistema 2+	
6a	Standard	EN 1090-1:2009 + A1:2011	
	Notified Body	SGS SPA - Milano (Italy) Certificato Nr.1381-CPR 507	
Declared performance			
7	Essential characteristics	Performance	Harmonized standard
	Dimensional tolerances	-	EN 1090-1:2009 + A1:2011
	Weldability	-	
	Crush resistance	-	
	Fire resistance	-	
	Reaction to fire	Class A1 according to standard EN 13501-1	
	Cadium release	-	
	Radioactivity emission	-	
	Durability	Galvanized surface as per standard EN ISO 1461. Galvanizing durability according to EN ISO 14713.	
	Project reference	-	
	Execution class	-	
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.		
MARENO DI PIAVE, 01/08/2016		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator	
DOP N. 4R02MGP Rev.1			