GRIDIRON®
BUILD YOUR CHANGES

GRIDIRON GROUP

CE UK CA

DECLARATION OF PERFORMANCE - CPR 305/2011

1	**Unique code of the product**	4R10SGPB
	Description	Vibro-compressed concrete channel MOD. R495, with galvanized protective edge rails, c/w S235JR steel pressure-locked grating, bearing bar 40x5 mm, transverse bar 10x3 mm, 33x11 mm heelguard mesh, installed and locked, hot-dip galvanized, dim. 490x1000 H40 mm. Channel runoff section sqcm. 1390. Load class C250 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	**Intended use or uses of the product**	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	**Manufacturer**	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	**Agent**	ND
5	**System of AVCP**	System 3
6	**Standard**	EN 1433:2008
	First year of marking	2016
	Notified Body	Istituto Giordano 00019 - Bellaria (RN)
Declared performance		
7	**Essential charateristics**	**Performance**
	Watertight	No loss
	Loading capacity:	
	Maximum load	C250 - EN 1433:2008
	Permanent set	<CO/300 - Cap. 7.16 Norm 1433:2008
	Durability	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	

MARENO DI PIAVE, -

Signed for and on behalf of the manufacturer
GIANCARLO ZANETTE
Administrator

DOP N. 4R10SGPB Rev.-