

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4RPOGPA
	Description	Pressure-locked grating with edges, 20x2-10x2 33x11, heelguard mesh, hot-dip galvanised, suitable for channel P150 LOWERED and POLY FLY 100. Load class C250 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	Sistema 2+
6a	Standard	EN 1090-1:2009 + A1:2011
	Notified Body	SGS SPA - Milano (Italy) Certificato Nr.1381-CPR 507
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	C250 - EN 1433:2008
	Permanent set	-
	Durability	Galvanized surface as per standard EN ISO 1461. Galvanizing durability according to EN ISO 14713.
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, 01/08/2016		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4RPOGPA Rev.1		