

DECLARATION OF PERFORMANCE - CPR 305/2011

16

1	Unique code of the product	4RPOGPB
	Description	Pressure locked grating 20x2-10x2 55x11, C-shaped framing with recesses for channel POLY FLY 100 and PLASTIC FLY 100, both with galvanized/stainless steel edges, P150 LOW, galvanized, loading class C250 accordingly to Standards UNI EN 1433:2008 norm as for installation instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	Sistema 2+
6a	Standard	EN 1090-1:2009 + A1:2011
	Notified Body	SGS SPA - Milano (Italy) Certificato Nr.1381-CPR 507

Declared performance

7	Essential characteristics	Performance	Harmonized standard
	Dimensional tolerances	-	EN 1090-1:2009 + A1:2011
	Weldability	-	
	Crush resistance	-	
	Fire resistance	-	
	Reaction to fire	Class A1 according to standard EN 13501-1	
	Cadium release	-	
	Radioactivity emission	-	
	Durability	Galvanized surface as per standard EN ISO 1461. Galvanizing durability according to EN ISO 14713.	
	Project reference	-	
	Execution class	-	

8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.
----------	---

MARENO DI PIAVE, 01/08/2016

DOP N. 4RPOGPB Rev.1

Signed for and on behalf of the manufacturer
GIANCARLO ZANETTE
Administrator

