

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4RP3SGPA
	Description	P265 additivated polymer concrete drain channel, with Gridiron's special galvanized edge rails, c/w pressure locked grating panel, in S235JR UNI EN 10025-2:2019 steel, bearing bar 30x3, transverse bar 10x2, mesh 33x11 (heelguard), dim. 265x1000, assembled and locked, hot-dip galvanized, runoff section cm ² 365. Loading class C250 accordingly to Standards UNI-EN 1433:2008 Norm as for installation instructions.
2	Intended use or uses of the product	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	System 3
6	Standard	EN 1433:2008
	First year of marking	2016
	Notified Body	Istituto Giordano 00019 - Bellaria (RN)
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	C250 - EN 1433:2008
	Permanent set	<CO/300 - Cap. 7.16 Norm 1433:2008
	Durability	NPD
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, - DOP N. 4RP3SGPA Rev.-		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator 