

DECLARATION OF PERFORMANCE - CPR 305/2011

1	Unique code of the product	4RP6MSP
	Description	P210 LOWERED additivated polymer concrete drain channel, with Gridiron's special galvanized edge rails, c/w plate embossed metal sheet 30/10, assembled and locked, hot-dip galvanized, runoff section sqcm. 89. Loading class C250 accordingly to Standards UNI-EN 1433:2008 Norm as for installation instructions.
2	Intended use or uses of the product	-
3	Manufacturer	GRIDIRON SPA Via E.Fermi - Z.I. RAMERA 31010 MARENO DI PIAVE (TV) Tel.:0438492502 - Fax:0438492545 Email: info@gridiron.it
4	Agent	ND
5	System of AVCP	-
6	Standard	-
	First year of marking	-
	Notified Body	-
Declared performance		
7	Essential characteristics	Performance
	Watertight	No loss
	Loading capacity:	
	Maximum load	C250 - EN 1433:2008
	Permanent set	-
	Durability	-
8	The performance of the product identified above is in conformity with the set of declared performances. This declaration of responsibility is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.	
MARENO DI PIAVE, -		Signed for and on behalf of the manufacturer GIANCARLO ZANETTE Administrator
DOP N. 4RP6MSP Rev.-		