



# TECHNICAL SHEET



<b>ASSEMBLED CODE</b>	4F00PZGLI
<b>DESCRIPTION</b>	Fiber reinforced concrete sump unit, L.500 mm, for channel MOD. VIBRO-BASE 100, c/w AISI 304 steel inlay press-formed metal sheet grating, 8 mm slots, Th. 12/10, installed, self-locking. Load class A15 according to EN 1433:2008 Norm, if installed following manufacturer instructions.
<b>PRODUCT LINE</b>	Fiber reinforced concrete sump units
<b>STANDARD</b>	EN 1433:2008
<b>INTENDED USE OR USES OF THE PRODUCT</b>	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
<b>DURABILITY</b>	Grades of weathering resistance: W +R (§6.3.3.3 EN 1433:2008)
<b>1) CHANNEL</b>	4F00PZ
<b>MATERIAL</b>	Constant flow concrete
<b>SERIES TYPE</b>	Vibrobase series 100
<b>SECTION TYPE</b>	H1
<b>PROFILE TYPE</b>	Without profiles
<b>VERSION TYPE</b>	Normal without built-in slope
<b>2) GRID</b>	4F05GLI
<b>MATERIAL</b>	Inox AISI 304 - X5 CrNi 18 10
<b>SURFACE FINISH</b>	None



Article dimensions mm	Inner width mm	Runoff section cmq	Bottom outlet mm	Weight Kg/each
500 x 170 x H 518	100	99	Ø125	61,4