

# TECHNICAL SHEET



<b>CODE</b>	4R02MGPA
<b>DESCRIPTION</b>	Press-locked grating panel, in S235JR UNI EN 10025-2:2019 steel, bearing bar 25x2, transverse bar 10x2, mesh 33x11 (heelguard), with C shaped edge, c/w 4 meshes for locking at R210 drain channel, hot-dip galvanized. Loading class C250 UNI EN 1433:2008.
<b>PRODUCT LINE</b>	Press-locked
<b>MATERIAL</b>	S235JR steel - EN 10025-2:2019
<b>SURFACE FINISH</b>	Hot Dip Galvanizing - UNI 1461
<b>STANDARD</b>	EN 1090-1:2009 + A1:2011
<b>INTENDED USE OR USES OF THE PRODUCT</b>	Collection and channelling of surface water into areas subject to pedestrian and/or vehicle traffic according to the indicated flow rate.
<b>DURABILITY</b>	Galvanized surface as per standard EN ISO 1461. Galvanizing durability according to EN ISO 14713.
<b>REACTION TO FIRE</b>	Class A1 according to standard EN 13501-1
<b>LOADING CLASS</b>	C250 - EN 1433:2008



Article dimensions mm	Weight Kg/each
210 x 500 x H 25	2,35